



CAVI RG
RG CABLES

www.klemi-contact.com

TEL. | +39 02 55.60.61.01

RG 179 - FEP



MIL C-17



COD: 1091

STRUTTURA - STRUCTURE

Mantello / Jacket	FEP (2,54 mm)
Conduttore / Conductor	Acciaio/CuAg ~ CuAg clad steel (0,3 mm) (7 x 0,10)
Isolante / Insulation	FEP (1,6)
1° schermo / Shield	Treccia Cu/Ag ~ Cu/Ag braid (2 mm)
2° isolante/ 2nd insulation	
2° schermo / Shield	
3° isolante/ 3th insulation	
Armatura / Armor	
Colore / Color	

Attenuazione - Attenuation

1 MHz	6,4 dB/100m
10 MHz	11,5 dB/100m
20 MHz	13,2 dB/100m
50 MHz	16,9 dB/100m
100 MHz	23,7 dB/100m
200 MHz	34,9 dB/100m
500 MHz	56,4 dB/100m
1000 MHz	85,2 dB/100m
2000 MHz	133,5 dB/100m
3000 MHz	163,0 dB/100m

PROPRIETÀ ELETTRICHE - ELECTRICAL PROPERTIES

Tensione nominale Voltage rating	
Impedenza caratteristica Characteristic impedance	75 ± 3 Ω
Velocità di propagazione Velocity ratio	0,7 v/c
Resistenza DC cond. int. Internal conductor DC resistance	784 Ω/km
Resistenza DC cond. est. External conductor DC resistance	56 Ω/km
Capacità / Capacity	63 pF/m

Return loss

5-50 MHz	> 24 dB
50-470 MHz	> 21 dB
> 470-1000 MHz	> 18 dB

PROPRIETÀ MECCANICHE - MECHANICAL PROPERTIES

Raggio curvatura dinamico Dynamic radius of curvature	30 mm
Raggio curvatura statico Static radius of curvature	15 mm
Max. carico trazione Max. tensile strength	55 N
Calore di combustione Heat of combustion	0,01 kWh/m
Temperatura operativa Operating temperature	-55 °C / +200 °C
Temperatura d'installazione Installation temperature	-5 °C / +55 °C
Resistenza UV UV resistance	★★★★

Certification:
CE: LVD
VDE: LVD
NSR/LVD 2014/35/EU



RG 6 - FRNC			8.43
RG 6 - PVC			8.43
RG 11 - FRNC			10
RG 11 - PVC			10
RG 11 Y - PE			10
RG 12 - FRNC			13.6
RG 12 - PVC			13.6
RG 22 - FRNC			10.67
RG 22 - PVC			10.67
RG 58 - FRNC			4.85
RG 58 - PE			4.85
RG 58 - PVC			4.85
RG 59 - PE			6.15
RG 59 - FRNC			6.15
RG 108			6
RG 142 - FEP			4.95
RG 164 - PE			22.1
RG 164 - PVC			22.1
RG 174 - PVC			2.8
RG 178			1.8
RG 179 - FEP			2.54
RG 180 - FEP			3.58
RG 187 - FEP			2.54



RG 188 - FEP			2.5
RG 195 - FEP			3.58
RG 196 - FEP			1.8
RG 213 - PE			10.3
RG 213 - FRNC			10.3
RG 213 - PVC			10.3
RG 214 - PE			10.8
RG 214 - FRNC			10.8
RG 214 - PVC			10.8
RG 215 - PVC			10.3
RG 216 - PE			18
RG 216 - PVC			18
RG 217 - PVC			13.8
RG 218 - FRNC			22.1
RG 218 - PVC			22.1
RG 219 - PVC			22.1
RG 223 - FRNC			5.38
RG 223 - PVC			5.38
RG 223 - PE			5.38
RG 303 - FEP			4.32
RG 316 - FEP			2.5
RG 316 - FEP			2.9

All Pictures shown are for illustration purpose only. Specifications are subject to change without notice

Le immagini sono inserite a scopo illustrativo. I prodotti possono subire modifiche.



ELECTRONIC
ELECTROMECHANICAL
COMPONENTS
PARTNER & DEALER



Via Monferrato, 43
20098 San Giuliano Milanese
I T A L Y

T. +39 02 55.60.61.01
F. +39 02 55.60.71.43

www.klemi-contact.com