


All rights are strictly reserved. Reproduction or disclosure to third parties in any form whatever is not permitted without written authorization from the proprietor. A violation is punishable.



Klemi Contact
The connectables

FUSE & FUSEHOLDER

340.000



ISO 8820-3



100 pz. - 1000 pz. - 2000 pz.

Body Corpo	BPT - GF 25	Blade material Materiale della lama	Zinc Zinco
Voltage Tensione	32 V	Contacts finishing Finitura contatti	Tin plated Stagnato
Breaking capacity Capacità di rottura	1000 A	Operating temp. Temp. operativa	-40° C / +125° C

TIME CURRENT / TEMPI DI FUSIONE

RATED CURRENT CORRENTE NOMINALE	1.10 x I _n		1.35 x I _n		2 x I _n		3.50 x I _n		2 x I _n	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
1 A - 40 A	100 h	∞	0.75 s	600 s	0.15 s	5 s	0.04 s	0.5 s	0.02 s	0.1 s

CODE	I. RATING I. NOM	i ² t [⊕]	V.D. C.D.T.	ISO CABLE SIZE ISO DIM. CAVO	COLOR COLORE
340.017	1 A	-	< 250 mV	0.35 mm ²	BLACK / NERO
340.020	2 A	157 A ² s	142 mV	0.35 mm ²	GREY / GRIGIO
340.022	3 A	200 A ² s	135 mV	0.35 mm ²	VIOLET / VIOLA
340.023	4 A	205 A ² s	126 mV	0.35 mm ²	PINK / ROSA
340.024	5 A	218 A ² s	119 mV	0.5 mm ²	BEIGE
340.026	7,5 A	304 A ² s	139 mV	0.75 mm ²	BROWN / MARRONE
340.027	10 A	320 A ² s	112 mV	1.0 mm ²	RED / ROSSO
340.029	15 A	480 A ² s	104 mV	1.5 mm ²	BLUE / BLU
340.031	20 A	720 A ² s	117 mV	2.5 mm ²	YELLOW / GIALLO
340.032 [⊖]	25 A	1155 A ² s	104 mV	2.5 mm ²	NATURAL / BIANCO
340.033 [⊖]	30 A	1843 A ² s	103 mV	4.0 mm ²	GREEN / VERDE
340.035	40 A	2880 A ² s	101 mV	6.0 mm ²	ORANGE / ARANCIONE

⊖ Body material: PSU - thermoplastic
Materiale del corpo fusibile: PSU - termoplastico

⊕ Calculated from breaking capacity test
Calcolato dal test di capacità di rottura

All Pictures shown are for illustration purpose only. Specifications are subject to change without notice

Le immagini sono inserite a scopo illustrativo. I prodotti possono subire modifiche.



ELECTRONIC
ELECTROMECHANICAL
COMPONENTS
PARTNER & DEALER



Via Monferrato, 43
20098 San Giuliano Milanese
I T A L Y

T. +39 02 55.60.61.01
F. +39 02 55.60.71.43

www.klemi-contact.com