


All rights are strictly reserved. Reproduction or disclosure to third parties in any form whatever is not permitted without written authorization from the proprietor. A violation is punishable.



Klemi Contact
The connectables

FUSE & FUSEHOLDER

341.100



ISO 8820-3



200 pz. - 500 pz. - 5000 pz.

Body Corpo	Polycarbonate Policarbonato	Blade material Materiale della lama	Zinc Zinco
Voltage Tensione	32 V	Contacts finishing Finitura contatti	Tin plated Stagnato
Breaking capacity Capacità di rottura	1000 A	Operating temp. Temp. operativa	-40° C / +125° C

TIME CURRENT / TEMPI DI FUSIONE

RATED CURRENT CORRENTE NOMINALE	1.10 x I _n		1.35 x I _n		2 x I _n		3.50 x I _n		6 x I _n	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
2 A - 30 A	100 h	∞	0.75 s	120 s	0.15 s	5 s	0.04 s	0.5 s	0.02 s	0.1 s

CODE	I. RATING I. NOM	t [⊖]	V.D. C.D.T.	ISO CABLE SIZE ISO DIM. CAVO	COLOR COLORE
341.120	2 A	135 A ² s	128 mV	0.35 mm ²	GREY / GRIGIO
341.122	3 A	115 A ² s	122 mV	0.35 mm ²	VIOLET / VIOLA
341.123	4 A	156 A ² s	121 mV	0.35 mm ²	PINK / ROSA
341.124	5 A	217 A ² s	112 mV	0.5 mm ²	BEIGE
341.126	7,5 A	256 A ² s	110 mV	0.75 mm ²	BROWN / MARRONE
341.127	10 A	387 A ² s	106 mV	1.0 mm ²	RED / ROSSO
341.129	15 A	720 A ² s	105 mV	1.5 mm ²	BLUE / BLU
341.131	20 A	980 A ² s	97 mV	2.5 mm ²	YELLOW / GIALLO
341.132 [⊖]	25 A	1344 A ² s	96 mV	2.5 mm ²	NATURAL / BIANCO
341.133 [⊖]	30 A	1692 A ² s	95 mV	4.0 mm ²	GREEN / VERDE

* Exceeds ISO requirements (600s)
Supera i requisiti ISO (600s)

⊖ **Body material: PSU - thermoplastic**
Materiale del corpo fusibile: PSU - termoplastico

⊖ **Calculated from breaking capacity test**
Calcolato dal test di capacità di rottura

All Pictures shown are for illustration purpose only. Specifications are subject to change without notice

Le immagini sono inserite a scopo illustrativo. I prodotti possono subire modifiche.



ELECTRONIC
ELECTROMECHANICAL
COMPONENTS
PARTNER & DEALER



Via Monferrato, 43
20098 San Giuliano Milanese
ITALY

T. +39 02 55.60.61.01
F. +39 02 55.60.71.43

www.klemi-contact.com