


All rights are strictly reserved. Reproduction or disclosure to third parties in any form whatever is not permitted without written authorization from the proprietor. A violation is punishable.



FUSE & FUSEHOLDER

341.200



STRIP

DIN 72581/2



Vibration class compliant with ISO 16750-3 test IV

Classe di vibrazione conforme alla norma ISO 16750-3 test IV



100 pz. - 1000 pz.

Body
Corpo

Zinc alloy
Lega di zinco

Breaking capacity
Capacità di rottura

1000 A

Voltage
Tensione

32 V

TIME CURRENT / TEMPI DI FUSIONE

RATED CURRENT CORRENTE NOMINALE	1.0xI _n		1.35xI _n		2xI _n		3.50xI _n		6xI _n	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
2 A - 30 A	4 h	∞	120 s	1800 s	1 s	15 s	0.3 s	5 s	0.1 s	1 s

CODE	I. RATING I. NOM	V.D. C.D.T.	THICKNESS SPESSORE
341.233	30 A	80 mV	0.20 mm
341.235	40 A	80 mV	0.25 mm
341.237	50 A	80 mV	0.35 mm
341.239	60 A	80 mV	0.40 mm
341.241	80 A	80 mV	0.50 mm
341.243	100 A	80 mV	0.55 mm

All Pictures shown are for illustration purpose only. Specifications are subject to change without notice

Le immagini sono inserite a scopo illustrativo. I prodotti possono subire modifiche.



ELECTRONIC
ELECTROMECHANICAL
COMPONENTS
PARTNER & DEALER



Via Monferrato, 43
20098 San Giuliano Milanese
I T A L Y

T. +39 02 55.60.61.01
F. +39 02 55.60.71.43

www.klemi-contact.com