


All rights are strictly reserved. Reproduction or disclosure to third parties in any form whatever is not permitted without written authorization from the proprietor. A violation is punishable.



Klemi Contact
The connectables

FUSE & FUSEHOLDER

341.900



RoHS
FREEMETAL

✓ **Also available without LED and/or in transparent material**
Disponibile anche senza LED e/o in materiale trasparente



200 pz. - 500 pz. - 5000 pz.

Body Corpo	Insulating plastic Plastica isolante	Blade material Materiale della lama	Zinc Zinco
Voltage Tensione	32 V	Contacts finishing Finitura contatti	Tin plated Stagnato

TIME CURRENT / TEMPI DI FUSIONE

RATED CURRENT CORRENTE NOMINALE	1.1 x I _n MAX	1.35 x I _n MAX	2 x I _n MAX
3 A - 30 A	100 h min.	1800 s	5 s

CODE	I. RATING I. NOM	COLD RESISTANCE RESISTENZA AL FREDDO	V.D. C.D.T.	COLOR COLORE
341.920	3 A	0.056 Ω	80 mV	GREY / GRIGIO
341.922	4 A	0.034 Ω	80 mV	VIOLET / VIOLA
341.923	5 A	0.024 Ω	80 mV	PINK / ROSA
341.924	7,5 A	0.018 Ω	80 mV	BEIGE
341.926	10 A	0.011 Ω	80 mV	BROWN / MARRONE
341.927	15 A	0.0073 Ω	80 mV	RED / ROSSO
341.929	20 A	0.0045 Ω	80 mV	BLUE / BLU
341.931	25 A	0.0032 Ω	80 mV	YELLOW / GIALLO
341.932	30 A	0.056 Ω	80 mV	NATURAL / BIANCO

All Pictures shown are for illustration purpose only. Specifications are subject to change without notice

Le immagini sono inserite a scopo illustrativo. I prodotti possono subire modifiche.



ELECTRONIC
ELECTROMECHANICAL
COMPONENTS
PARTNER & DEALER



Via Monferrato, 43
20098 San Giuliano Milanese
I T A L Y

T. +39 02 55.60.61.01
F. +39 02 55.60.71.43

www.klemi-contact.com