All right are strictly reserved. Reproduction or disclosure to third parties in any form whatever is not permitted without written authorization from the proprietor. A violation is punishable

Klemi Contact
The connectables

FUSE & FUSEHOLDER

343.400



REACH

RoHS

ISO 8820-3

100 pz. - 1000 pz. - 2000 pz.

Body Corpo	PA66 - GF 25	**Blade material** Materiale della lama	Zinc Zinco
Voltage Tensione	32 V	**Contacts finishing** Finitura contatti	Tin plated Stagnato
Breaking capacity Capacità di rottura	1000 A	**Operating temp.** Temp. operativa	-40° C / +125° C

TIME CURRENT / TEMPI DI FUSIONE

RATED CURRENT CORRENTE NOMINALE	1.00 x In		1.35 x In		2 x In		3.50 x In		6 x In	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
1 A ~ 40 A	100 h	∞	60 s	600 s	2 s	60 s	0.2 s	7 s	0.04 s	1 s

CODE	I. RATING I. NOM	i²t ❷	V.D. C.D.T.	ISO CABLE SIZE ISO DIM. CAVO	COLOR COLORE
343.431	30 A	7069 A²s	95 mV	4.0 mm²	GREEN / VERDE
343.433	40 A	23120 A²s	90 mV	4.0 mm²	ORANGE / ARANCIONE
343.435	50 A	36980 A²s	89 mV	6.0 mm²	RED / ROSSO
343.439	60 A	40680 A²s	84 mV	6.0 mm²	BLUE / BLU
343.440	70 A	112500 A²s	87 mV	10.0 mm²	BEIGE
343.441	80 A	23120 A²s	85 mV	10.0 mm²	NATURAL / BIANCO
343.443	100 A	65000 A²s	89.5 mV	16.0 mm²	VIOLET / VIOLA

❷ **Calculated from breaking capacity test**
Calcolato dal test di capacità di rottura

All Pictures shown are for illustration purpose only. Specifications are subject to change without notice

Le immagini sono inserite a scopo illustrativo. I prodotti possono subire modifiche.

Klemi Contact
The connectables

ELECTRONIC
ELECTROMECHANICAL
COMPONENTS
PARTNER & DEALER

Klemi Contact
The connectables

Via Monferrato, 43
20098 San Giuliano Milanese
ITALY

T. +39 02 55.60.61.01
F. +39 02 55.60.71.43

www.klemi-contact.com