


All rights are strictly reserved. Reproduction or disclosure to third parties in any form whatever is not permitted without written authorization from the proprietor. A violation is punishable.



Klemi Contact
The connectables

FUSE & FUSEHOLDER

520.000



F **DIN 41.571-1** **ac/dc**

As assembly with two pigtailed on various form and length
Assemblato con due cappucci con terminali a lunghezza custom



10 pz. [std. packaging ~ conf. standard]
1000 pz. [ind. packaging ~ conf. industriale]

Body Corpo	Glass Vetro	Extinguishing agent Polvere spegnciarco	<input checked="" type="checkbox"/>
Voltage Tensione	250 V	Contacts material Materiale contatti	CuZn
Soldering Saldatura	EN 60068-2-20	Contacts finishing Finitura contatti	Ni

TIME CURRENT / TEMPI DI FUSIONE

RATED CURRENT CORRENTE NOMINALE	1.5 x I _n MAX	2.1 x I _n MAX	4 x I _n MAX	10 x I _n MAX
500 mA - 16 A	1 h	30 min	300 ms	20 ms

CODE	I. RATING I. NOM	BREAKING CAPACITY CAPACITÀ DI ROTTURA	VOLTAGE DROP CADUTA DI TENSIONE	POW. DIS. POT. DIS.
520.014	500 mA	80 A ac / 20 A dc	1000 mV	A rich. / On req.
520.015	630 mA	80 A ac / 20 A dc	630 mV	A rich. / On req.
520.016	800 mA	80 A ac / 20 A dc	240 mV	A rich. / On req.
520.017	1 A	1000 A ac / 250 A dc	200 mV	A rich. / On req.
520.018	1,25 A	1000 A ac / 250 A dc	190 mV	A rich. / On req.
520.019	1,6 A	1000 A ac / 250 A dc	480 mV	1.28 W
520.020	2 A	1000 A ac / 250 A dc	400 mV	4.96 W
520.021	2,5 A	1000 A ac / 250 A dc	400 mV	7.07 W
520.022	3,15 A	1000 A ac / 250 A dc	400 mV	11.61 W
520.023	4 A	1000 A ac / 250 A dc	240 mV	19.84 W
520.024	5 A	300 A ac / -	240 mV	38.5 W
520.025	6,3 A	1000 A ac / 250 A dc	230 mV	59.53 W
520.026	8 A	300 A ac / -	170 mV	124.8 W
520.027	10 A	300 A ac / -	160 mV	220 W
520.028	12.5 A	300 A ac / -	150 mV	434.38 W
520.030	16 A	300 A ac / -	130 mV	709.97 W

ⓘ Not mentioned in the standards
Non menzionato negli standards

All Pictures shown are for illustration purpose only. Specifications are subject to change without notice

Le immagini sono inserite a scopo illustrativo. I prodotti possono subire modifiche.



ELECTRONIC
ELECTROMECHANICAL
COMPONENTS
PARTNER & DEALER



Via Monferrato, 43
20098 San Giuliano Milanese
ITALY

T. +39 02 55.60.61.01
F. +39 02 55.60.71.43

www.klemi-contact.com