


All rights are strictly reserved. Reproduction or disclosure to third parties in any form whatever is not permitted without written authorization from the proprietor. A violation is punishable.



**Klemi Contact**  
*The connectables*

**FUSE & FUSEHOLDER**

## 520.100



**RoHS**  
REACH

**FF** IEC 60127-2/A2 **ac**

As assembly with two pigtails on various form and length  
Assemblato con due cappucci con terminali a lunghezza custom



10 pz. [std. packaging ~ conf. standard]  
1000 pz. [ind. packaging ~ conf. industriale]

<b>Body</b> Corpo	100 mA ~ 1,25 A	Glass Vetro	<b>Body</b> Corpo	1,6 A ~ 16 A	Ceramic Ceramica
<b>Voltage</b> Tensione	250 V		<b>Contacts material</b> Materiale contatti	CuZn	
<b>Soldering</b> Saldatura	EN 60068-2-20		<b>Contacts finishing</b> Finitura contatti		

### TIME CURRENT / TEMPI DI FUSIONE

RATED CURRENT CORRENTE NOMINALE	1 x I <sub>n</sub>		1.5 x I <sub>n</sub>		2.75 x I <sub>n</sub>		4 x I <sub>n</sub>		10 x I <sub>n</sub>	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
100 mA - 16 A	1 h	30 min	2 ms	150 ms	1 ms	50 ms	10 ms			

CODE	I. RATING I. NOM	BREAKING CAPACITY CAPACITÀ DI ROTTURA	VOLTAGE DROP CADUTA DI TENSIONE	MELTING RATING FUSIONE NOM.
520.107	100 mA	35 A	3500 mV	0.0020 A <sup>2</sup> s
520.108	125 mA	35 A	3000 mV	0.0031 A <sup>2</sup> s
520.109	160 mA	35 A	3000 mV	0.0051 A <sup>2</sup> s
520.110	200 mA	35 A	2500 mV	0.0104 A <sup>2</sup> s
520.111	250 mA	35 A	2500 mV	0.0312 A <sup>2</sup> s
520.112	315 mA	35 A	2000 mV	0.0674 A <sup>2</sup> s
520.113	400 mA	35 A	1500 mV	0.0960 A <sup>2</sup> s
520.114	500 mA	35 A	1500 mV	0.1700 A <sup>2</sup> s
520.115	630 mA	35 A	750 mV	0.1600 A <sup>2</sup> s
520.116	800 mA	35 A	750 mV	0.3200 A <sup>2</sup> s
520.117	1 A	35 A	250 mV	0.5400 A <sup>2</sup> s
520.118	1,25 A	35 A	250 mV	1.2500 A <sup>2</sup> s
520.119	1,6 A	1500 A	1000 mV	0.2600 A <sup>2</sup> s
520.120	2 A	1500 A	700 mV	1.9200 A <sup>2</sup> s
520.121	2,5 A	1500 A	700 mV	2.7500 A <sup>2</sup> s
520.122	3,15 A	1500 A	600 mV	3.7700 A <sup>2</sup> s
520.123	4 A	1500 A	600 mV	6.4000 A <sup>2</sup> s
520.124	5 A	1500 A	500 mV	12.5000 A <sup>2</sup> s
520.125	6,3 A	1500 A	500 mV	19.8500 A <sup>2</sup> s
520.126	8 A	1500 A	400 mV	33.2800 A <sup>2</sup> s
520.127	10 A	1500 A	400 mV	60.0000 A <sup>2</sup> s
520.128	12,5 A	1500 A	300 mV	62.5000 A <sup>2</sup> s
520.130	16 A	1500 A	300 mV	A rich. / On req.

All Pictures shown are for illustration purpose only. Specifications are subject to change without notice

Le immagini sono inserite a scopo illustrativo. I prodotti possono subire modifiche.



ELECTRONIC  
ELECTROMECHANICAL  
COMPONENTS  
PARTNER & DEALER



Via Monferrato, 43  
20098 San Giuliano Milanese  
I T A L Y

T. +39 02 55.60.61.01  
F. +39 02 55.60.71.43

[www.klemi-contact.com](http://www.klemi-contact.com)