


All rights are strictly reserved. Reproduction or disclosure to third parties in any form whatever is not permitted without written authorization from the proprietor. A violation is punishable.



Klemi Contact
The connectables

FUSE & FUSEHOLDER

525.200



M FABRIQUE NORM. **ac**

As assembly with two pigtailed on various form and length
Assemblato con due cappucci con terminali a lunghezza custom



10 pz. [std. packaging ~ conf. standard]
1000 pz. [ind. packaging ~ conf. industriale]

Body Corpo	Glass Vetro	Extinguishing agent Polvere spegniarco	1,6 A ~ 10 A
Voltage Tensione	250 V	Contacts material Materiale contatti	CuZn
Soldering Saldatura	EN 60068-2-20	Contacts finishing Finitura contatti	Ni

TIME CURRENT / TEMPI DI FUSIONE

RATED CURRENT CORRENTE NOMINALE	1,5 x I _n		2,1 x I _n		4 x I _n		10 x I _n	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
40 mA - 1,25 A 1,6 A - 16 A	1 h	1 h	10 min 30 min		40 ms 40 ms	2000 ms 2000 ms	5 ms	90 ms 90 ms

CODE	I. RATING I. NOM	BREAKING CAPACITY CAPACITÀ DI ROTTURA	VOLTAGE DROP CADUTA DI TENSIONE	POW. DIS. POT. DIS.
525.203	40 mA	80 A	2000 mV	A rich./Onreq.
525.204	50 mA	80 A	1500 mV	A rich./Onreq.
525.205	63 mA	80 A	1400 mV	A rich./Onreq.
525.206	80 mA	80 A	900 mV	A rich./Onreq.
525.207	100 mA	80 A	600 mV	A rich./Onreq.
525.208	125 mA	80 A	400 mV	A rich./Onreq.
525.209	160 mA	80 A	400 mV	A rich./Onreq.
525.210	200 mA	80 A	400 mV	A rich./Onreq.
525.211	250 mA	80 A	400 mV	A rich./Onreq.
525.212	315 mA	80 A	300 mV	A rich./Onreq.
525.213	400 mA	80 A	300 mV	A rich./Onreq.
525.214	500 mA	80 A	300 mV	A rich./Onreq.
525.215	630 mA	80 A	300 mV	A rich./Onreq.
525.216	800 mA	80 A	300 mV	A rich./Onreq.
525.217	1 A	80 A	250 mV	A rich./Onreq.
525.218	1,25 A	80 A	250 mV	A rich./Onreq.
525.219	1,6 A	80 A	300 mV	A rich./Onreq.
525.220	2 A	80 A	300 mV	A rich./Onreq.
525.221	2,5 A	80 A	300 mV	A rich./Onreq.
525.222	3,15 A	80 A	300 mV	A rich./Onreq.
525.223	4 A	80 A	300 mV	A rich./Onreq.
525.224	5 A	80 A	250 mV	A rich./Onreq.
525.225	6,3 A	80 A	250 mV	A rich./Onreq.
525.226	8 A	80 A	200 mV	A rich./Onreq.
525.227	10 A	100 A	200 mV	A rich./Onreq.
525.228	12,5 A	125 A	200 mV	A rich./Onreq.
525.230	16 A	160 A	200 mV	A rich./Onreq.

All Pictures shown are for illustration purpose only. Specifications are subject to change without notice

Le immagini sono inserite a scopo illustrativo. I prodotti possono subire modifiche.



ELECTRONIC
ELECTROMECHANICAL
COMPONENTS
PARTNER & DEALER



Via Monferrato, 43
20098 San Giuliano Milanese
I T A L Y

T. +39 02 55.60.61.01
F. +39 02 55.60.71.43

www.klemi-contact.com