


All rights are strictly reserved. Reproduction or disclosure to third parties in any form whatever is not permitted without written authorization from the proprietor. A violation is punishable.



Klemi Contact
The connectables

FUSE & FUSEHOLDER

525.300



RoHS
REACH

T FABRIQUE NORM. ac

As assembly with two pigtails on various form and length
Assemblato con due cappucci con terminali a lunghezza custom



10 pz. [std. packaging ~ conf. standard]
1000 pz. [ind. packaging ~ conf. industriale]

Body Corpo	Glass Vetro	Extinguishing agent Polvere spegnciarco	1,6 A ~ 10 A
Voltage Tensione	250 V	Contacts material Materiale contatti	CuZn
Soldering Saldatura	EN 60068-2-20	Contacts finishing Finitura contatti	Ni

TIME CURRENT / TEMPI DI FUSIONE

RATED CURRENT CORRENTE NOMINALE	1.5 x I _n		2.1 x I _n		4 x I _n		10 x I _n	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
32 mA ~ 100 mA 125 mA ~ 16 A	60 min	120 s	300 ms	10 s	40 ms	3 s	10 ms	300 ms
	60 min	120 s	600 ms	10 s	150 ms	3 s	20 ms	300 ms

CODE	I. RATING I. NOM	BREAKING CAPACITY CAPACITÀ DI ROTTURA	VOLTAGE DROP CADUTA DI TENSIONE	MELTING RATING FUSIONE NOM.
525.302	32 mA	80 A	5000 mV	A rich./On req.
525.303	40 mA	80 A	4000 mV	A rich./On req.
525.304	50 mA	80 A	3500 mV	A rich./On req.
525.305	63 mA	80 A	3000 mV	A rich./On req.
525.306	80 mA	80 A	3000 mV	A rich./On req.
525.307	100 mA	80 A	2500 mV	A rich./On req.
525.308	125 mA	80 A	2000 mV	A rich./On req.
525.309	160 mA	80 A	1900 mV	A rich./On req.
525.310	200 mA	80 A	1500 mV	A rich./On req.
525.311	250 mA	80 A	1300 mV	A rich./On req.
525.312	315 mA	80 A	1100 mV	A rich./On req.
525.313	400 mA	80 A	1000 mV	A rich./On req.
525.314	500 mA	80 A	900 mV	A rich./On req.
525.315	630 mA	80 A	300 mV	A rich./On req.
525.316	800 mA	80 A	250 mV	A rich./On req.
525.317	1 A	80 A	150 mV	A rich./On req.
525.318	1,25 A	80 A	150 mV	A rich./On req.
525.319	1,6 A	80 A	150 mV	A rich./On req.
525.320	2 A	80 A	150 mV	A rich./On req.
525.321	2,5 A	80 A	120 mV	A rich./On req.
525.322	3,15 A	80 A	100 mV	A rich./On req.
525.323	4 A	80 A	100 mV	A rich./On req.
525.324	5 A	80 A	100 mV	A rich./On req.
525.325	6,3 A	80 A	100 mV	A rich./On req.
525.326	8 A	80 A	130 mV	A rich./On req.
525.327	10 A	80 A	120 mV	A rich./On req.
525.328	12,5 A	80 A	100 mV	A rich./On req.
525.330	16 A	80 A	80 mV	A rich./On req.

All Pictures shown are for illustration purpose only. Specifications are subject to change without notice

Le immagini sono inserite a scopo illustrativo. I prodotti possono subire modifiche.



ELECTRONIC
ELECTROMECHANICAL
COMPONENTS
PARTNER & DEALER



Via Monferrato, 43
20098 San Giuliano Milanese
I T A L Y

T. +39 02 55.60.61.01
F. +39 02 55.60.71.43

www.klemi-contact.com