



All rights are strictly reserved. Reproduction or disclosure to third parties in any form whatever is not permitted without written authorization from the proprietor. A violation is punishable.



Klemi Contact
The connectables

FUSE & FUSEHOLDER

525.600



RoHS
TECHNOLOGIC

F FABRIQUE NORM. ac

As assembly with two pigtailed on various form and length
Assemblato con due cappucci con terminali a lunghezza custom



10 pz. [std. packaging ~ conf. standard]
1000 pz. [ind. packaging ~ conf. industriale]

Body Corpo	Glass Vetro	Extinguishing agent Polvere spegniarico	1,6 A ~ 10 A
Voltage Tensione	250 V	Contacts material Materiale contatti	CuZn
Soldering Saldatura	EN 60068-2-20	Contacts finishing Finitura contatti	Ni

TIME CURRENT / TEMPI DI FUSIONE

RATED CURRENT CORRENTE NOMINALE	1,5 x I _n		2,1 x I _n		4 x I _n		10 x I _n	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
32 mA - 6,3 A 8 A - 16 A	1 h	1 h	0	30 min	0	300 ms	0	20 ms
				30 min		300 ms		30 ms

CODE	I. RATING I. NOM	BREAKING CAPACITY CAPACITÀ DI ROTTURA	VOLTAGE DROP CADUTA DI TENSIONE	MELTING RATING FUSIONE NOM.
525.602	32 mA	35 A	10.000 mV	A rich./Onreq.
525.603	40 mA	35 A	10.000 mV	A rich./Onreq.
525.604	50 mA	35 A	9000 mV	A rich./Onreq.
525.605	63 mA	35 A	8000 mV	A rich./Onreq.
525.606	80 mA	35 A	5000 mV	A rich./Onreq.
525.607	100 mA	35 A	3000 mV	0.00390 A ² s
525.608	125 mA	35 A	2500 mV	0.0084 A ² s
525.609	160 mA	35 A	2500 mV	0.0154 A ² s
525.610	200 mA	35 A	2000 mV	0.0292 A ² s
525.611	250 mA	35 A	2000 mV	0.0650 A ² s
525.612	315 mA	35 A	2000 mV	0.16 A ² s
525.613	400 mA	35 A	1500 mV	0.26 A ² s
525.614	500 mA	35 A	1000 mV	0.25 A ² s
525.615	630 mA	35 A	1000 mV	0.47 A ² s
525.616	800 mA	35 A	1000 mV	A rich./Onreq.
525.617	1 A	35 A	500 mV	1.16 A ² s
525.618	1,25 A	35 A	300 mV	2.03 A ² s
525.619	1,6 A	35 A	300 mV	1.28 A ² s
525.620	2 A	35 A	300 mV	5.76 A ² s
525.621	2,5 A	35 A	300 mV	8.13 A ² s
525.622	3,15 A	35 A	300 mV	13.30 A ² s
525.623	4 A	40 A	250 mV	21.12 A ² s
525.624	5 A	50 A	220 mV	42.25 A ² s
525.625	6,3 A	63 A	200 mV	103.59 A ² s
525.626	8 A	80 A	200 mV	126.72 A ² s
525.627	10 A	100 A	180 mV	208.00 A ² s
525.628	12,5 A	125 A	150 mV	A rich./Onreq.
525.630	16 A	160 A	150 mV	A rich./Onreq.

All Pictures shown are for illustration purpose only. Specifications are subject to change without notice

Le immagini sono inserite a scopo illustrativo. I prodotti possono subire modifiche.



ELECTRONIC
ELECTROMECHANICAL
COMPONENTS
PARTNER & DEALER



Via Monferrato, 43
20098 San Giuliano Milanese
I T A L Y

T. +39 02 55.60.61.01
F. +39 02 55.60.71.43

www.klemi-contact.com