

All rights are strictly reserved. Reproduction or disclosure to third parties in any form whatever is not permitted without written authorization from the proprietor. A violation is punishable.



Klemi Contact
The connectables

FUSE & FUSEHOLDER

527.000



RoHS
REACH

F **DIN 41.576-1** **ac**



10 pz. [std. packaging ~ conf. standard]
1000 pz. [ind. packaging ~ conf. industriale]

Body Corpo	Ceramic Ceramica	Extinguishing agent Polvere spegniarico	<input checked="" type="checkbox"/>
Voltage Tensione	250 V	Contacts material Materiale contatti	CuZn
		Contacts finishing Finitura contatti	Ni

TIME CURRENT / TEMPI DI FUSIONE

RATED CURRENT CORRENTE NOMINALE	1,5 x I _n MIN	2,1 x I _n MAX	4 x I _n MAX	10 x I _n MAX
1,6 A - 10 A	1 h	30 min	300 ms	20 ms

CODE	I. RATING I. NOM	BREAKING CAPACITY CAPACITÀ DI ROTTURA	VOLTAGE DROP CADUTA DI TENSIONE	POW. DIS. POT. DIS.
527.019	1,6 A	300 A	640 mV	A rich./Onreq.
527.020	2 A	300 A	420 mV	A rich./Onreq.
527.021	2,5 A	300 A	320 mV	A rich./Onreq.
527.022	3,15 A	300 A	250 mV	A rich./Onreq.
527.023	4 A	300 A	200 mV	A rich./Onreq.
527.024	5 A	300 A	180 mV	A rich./Onreq.
527.025	6,3 A	300 A	170 mV	A rich./Onreq.
527.026 ^⓪	8 A	300 A	150 mV	A rich./Onreq.
527.027 ^⓪	10 A	300 A	150 mV	A rich./Onreq.

^⓪ Not mentioned in the standards
Non menzionato negli standards

All Pictures shown are for illustration purpose only. Specifications are subject to change without notice

Le immagini sono inserite a scopo illustrativo. I prodotti possono subire modifiche.



ELECTRONIC
ELECTROMECHANICAL
COMPONENTS
PARTNER & DEALER



Via Monferrato, 43
20098 San Giuliano Milanese
I T A L Y

T. +39 02 55.60.61.01
F. +39 02 55.60.71.43

www.klemi-contact.com