


All rights are strictly reserved. Reproduction or disclosure to third parties in any form whatever is not permitted without written authorization from the proprietor. A violation is punishable.



**Klemi Contact**  
*The connectables*

**FUSE & FUSEHOLDER**

515.300



**T** IEC 60127-2/A2 **ac**

As assembly with two pigtailed on various form and length  
Assemblato con due cappucci con terminali a lunghezza custom



100 pz. [std. packaging ~ conf. standard]  
1000 pz. [ind. packaging ~ conf. industriale]

<b>Body</b> Corpo	Glass Vetro	<b>Extinguishing agent</b> Polvere spegنيarco	<input checked="" type="checkbox"/>
<b>Voltage</b> Tensione	125 V ~ 250 V	<b>Contacts material</b> Materiale contatti	CuZn
<b>Soldering</b> Saldatura	EN 60068-2-20	<b>Contacts finishing</b> Finitura contatti	Ni

**TIME CURRENT / TEMPI DI FUSIONE**

RATED CURRENT CORRENTE NOMINALE	1.5 x I <sub>n</sub>		2.75 x I <sub>n</sub>		4 x I <sub>n</sub>		10 x I <sub>n</sub>	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
250 mA - 6,3 A	1 h		400ms	10 s	150 ms	3 s	20ms	300ms

CODE	I. RATING I. NOM	BREAKING CAPACITY CAPACITÀ DI ROTTURA	VOLTAGE DROP CADUTA DI TENSIONE	VOLTAGE TENSIONE
515.311	250 mA	35 A	300 mV	250 V
515.312	315 mA	35 A	200 mV	250 V
515.313	400 mA	35 A	100 mV	250 V
515.314	500 mA	35 A	150 mV	250 V
515.315	630 mA	35 A	150 mV	250 V
515.316	800 mA	35 A	150 mV	250 V
515.317	1 A	35 A	150 mV	250 V
515.318	1,25 A	35 A	100 mV	250 V
515.359	1,5 A	35 A	100 mV	250 V
515.320	2 A	35 A	100 mV	250 V
515.321	2,5 A	35 A	100 mV	250 V
515.365	3,5 A	35 A	100 mV	250 V
515.323	4 A	40 A	100 mV	125 V
515.324	5 A	50 A	100 mV	125 V
515.366	6 A	60 A	100 mV	125 V
515.325	6,3 A	63 A	100 mV	125 V

All Pictures shown are for illustration purpose only. Specifications are subject to change without notice

Le immagini sono inserite a scopo illustrativo. I prodotti possono subire modifiche.



ELECTRONIC  
ELECTROMECHANICAL  
COMPONENTS  
PARTNER & DEALER



Via Monferrato, 43  
20098 San Giuliano Milanese  
I T A L Y

T. +39 02 55.60.61.01  
F. +39 02 55.60.71.43

[www.klemi-contact.com](http://www.klemi-contact.com)