


All rights are strictly reserved. Reproduction or disclosure to third parties in any form whatever is not permitted without written authorization from the proprietor. A violation is punishable.



**Klemi Contact**  
*The connectables*

**FUSE & FUSEHOLDER**

**520.500**



**F** EN 60127-2-1 **DIN 41.660** ac

As assembly with two pigtailed on various form and length  
Assemblato con due cappucci con terminali a lunghezza custom



10 pz. [std. packaging ~ conf. standard]  
1000 pz. [ind. packaging ~ conf. industriale]

<b>Body</b> Corpo	Ceramic Ceramica	<b>Extinguishing agent</b> Polvere spegnciarco	<input checked="" type="checkbox"/>
<b>Voltage</b> Tensione	250 V	<b>Contacts material</b> Materiale contatti	CuZn
<b>Soldering</b> Saldatura	EN 60068-2-20	<b>Contacts finishing</b> Finitura contatti	Ni

**TIME CURRENT / TEMPI DI FUSIONE**

RATED CURRENT CORRENTE NOMINALE	1.5 x I <sub>n</sub>		2.1 x I <sub>n</sub>		2.75 x I <sub>n</sub>		4 x I <sub>n</sub>		10 x I <sub>n</sub>	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
50 mA - 3.15 A	60 min	30 min	10 min	2 s	3 ms	300 ms	0	20 ms		
4 A - 10 A	60 min	30 min	10 min	3 s	3 ms	300 ms	0	20 ms		
12.5 A - 16 A	60 min	30 min	40 min	20 s	10 ms	1 s	0	30 ms		

CODE	I. RATING I. NOM.	BREAKING CAPACITY CAPACITÀ DI ROTTURA	V.D. C.D.T.	POW. DIS. POT. DIS.	MELTING RATING FUSIONE NOM.
520.504	50 mA	1500 A	10.000 mV	1.6 W	0.00016 A <sup>2</sup> s
520.505	63 mA	1500 A	8800 mV	1.6 W	0.00034 A <sup>2</sup> s
520.506	80 mA	1500 A	7600 mV	1.6 W	0.00064 A <sup>2</sup> s
520.507	100 mA	1500 A	7000 mV	1.6 W	0.0035 A <sup>2</sup> s
520.508	125 mA	1500 A	5000 mV	1.6 W	0.0059 A <sup>2</sup> s
520.509	160 mA	1500 A	4300 mV	1.6 W	0.055 A <sup>2</sup> s
520.510	200 mA	1500 A	3500 mV	1.6 W	0.016 A <sup>2</sup> s
520.511	250 mA	1500 A	2800 mV	2.5 W	0.046 A <sup>2</sup> s
520.512	315 mA	1500 A	2500 mV	2.5 W	0.072 A <sup>2</sup> s
520.513	400 mA	1500 A	2000 mV	2.5 W	0.25 A <sup>2</sup> s
520.514	500 mA	1500 A	1800 mV	2.5 W	0.17 A <sup>2</sup> s
520.515	630 mA	1500 A	1500 mV	2.5 W	0.11 A <sup>2</sup> s
520.516	800 mA	1500 A	1200 mV	2.5 W	0.18 A <sup>2</sup> s
520.517	1 A	1500 A	1000 mV	2.5 W	0.17 A <sup>2</sup> s
520.518	1,25 A	1500 A	800 mV	4.0 W	0.58 A <sup>2</sup> s
520.519	1,6 A	1500 A	600 mV	4.0 W	0.89 A <sup>2</sup> s
520.520	2 A	1500 A	500 mV	4.0 W	1.91 A <sup>2</sup> s
520.521	2,5 A	1500 A	400 mV	4.0 W	2.61 A <sup>2</sup> s
520.522	3,15 A	1500 A	350 mV	4.0 W	2.68 A <sup>2</sup> s
520.523	4 A	1500 A	300 mV	4.0 W	12.9 A <sup>2</sup> s
520.524	5 A	1500 A	250 mV	4.0 W	31.2 A <sup>2</sup> s
520.525	6,3 A	1500 A	200 mV	4.0 W	79.3 A <sup>2</sup> s
520.526	8 A	1500 A	200 mV	4.0 W	86.7 A <sup>2</sup> s
520.527	10 A	1500 A	200 mV	4.0 W	204.4 A <sup>2</sup> s
520.528	12.5 A	1500 A	200 mV	4.0 W	433.3 A <sup>2</sup> s
520.530	16 A	1500 A	200 mV	4.0 W	930.6 A <sup>2</sup> s

- ① Not mentioned in the standards / Non menzionato negli standards
- ② No Semko approval / Senza omologazione Semko
- ③ No cURus approval / Senza omologazione cURus

All Pictures shown are for illustration purpose only. Specifications are subject to change without notice

Le immagini sono inserite a scopo illustrativo. I prodotti possono subire modifiche.



ELECTRONIC  
ELECTROMECHANICAL  
COMPONENTS  
PARTNER & DEALER



Via Monferrato, 43  
20098 San Giuliano Milanese  
I T A L Y

T. +39 02 55.60.61.01  
F. +39 02 55.60.71.43

[www.klemi-contact.com](http://www.klemi-contact.com)