


All rights are strictly reserved. Reproduction or disclosure to third parties in any form whatever is not permitted without written authorization from the proprietor. A violation is punishable.



Klemi Contact
The connectables

FUSE & FUSEHOLDER

520.600



F **EN 60127-2-2** **DIN 41.661** **ac**

As assembly with two pigtails on various form and lenght
Assemblato con due cappucci con terminali a lunghezza custom

100 pz. [std. packaging ~ conf. standard]
1000 pz. [ind. packaging ~ conf. industriale]

Body Corpo	Glass Vetro	Extinguishing agent Polvere spegniarco	<input checked="" type="checkbox"/>
Voltage Tensione	250 V	Contacts material Materiale contatti	CuZn
Soldering Saldatura	EN 60068-2-20	Contacts finishing Finitura contatti	Ni

TIME CURRENT / TEMPI DI FUSIONE

RATED CURRENT CORRENTE NOMINALE	2.1 x I _n		2.75 x I _n		4 x I _n		10 x I _n
	MAX		MIN	MAX	MIN	MAX	MAX
32 - 100 mA 125 mA - 6.3 A 8 A - 10 A	30 min	30 min	10 ms	500 ms	3 ms	100 ms	20 ms
	30 min	30 min	50 ms	2 s	10 ms	300 ms	20 ms
	30 min	30 min	50 ms	2 s	10 ms	400 ms	40 ms

CODE	I. RATING I. NOM	BREAKING CAPACITY CAPACITÀ DI ROTTURA	VOLTAGE DROP CADUTA DI TENSIONE	POW. DIS. POT. DIS.
520.602	32 mA	35 A	10000 mV	1.6W
520.603	40 mA	35 A	8000 mV	1.6W
520.604	50 mA	35 A	7000 mV	1.6W
520605	63 mA	35 A	5000 mV	1.6W
520.606	80 mA	35 A	4000 mV	1.6W
520.607	100 mA	35 A	3500 mV	1.6W
520.608	125 mA	35 A	2000 mV	1.6W
520.609	160 mA	35 A	2000 mV	1.6W
520.610	200 mA	35 A	1700 mV	1.6W
520.611	250 mA	35 A	1400 mV	1.6W
520.612	315 mA	35 A	1300 mV	1.6W
520.613	400 mA	35 A	1200 mV	1.6W
520.614	500 mA	35 A	1000 mV	1.6W
520.615	630 mA	35 A	650 mV	1.6W
520.616	800 mA	35 A	240 mV	1.6W
520.617	1 A	35 A	200 mV	1.6W
520.618	1,25 A	35 A	200 mV	1.6W
520.619	1,6 A	35 A	190 mV	1.6W
520.620	2 A	35 A	170 mV	1.6W
520.621	2,5 A	35 A	170 mV	1.6W
520.622	3,15 A	35 A	150 mV	2.5W
520.623	4 A	40A	130 mV	2.5W
520.624	5 A	50A	130 mV	2.5W
520.625	6,3 A	63A	130 mV	2.5W
520.626 ^⓪	8 A	80A	130 mV	4 W
520.627 ^⓪	10 A	100A	130 mV	4 W

^⓪ Voltage: 125 V
Tensione: 125 V

All Pictures shown are for illustration purpose only. Specifications are subject to change without notice

Le immagini sono inserite a scopo illustrativo. I prodotti possono subire modifiche.



ELECTRONIC
ELECTROMECHANICAL
COMPONENTS
PARTNER & DEALER



Via Monferrato, 43
20098 San Giuliano Milanese
I T A L Y

T. +39 02 55.60.61.01
F. +39 02 55.60.71.43

www.klemi-contact.com