


All rights are strictly reserved. Reproduction or disclosure to third parties in any form whatever is not permitted without written authorization from the proprietor. A violation is punishable.



Klemi Contact
The connectables

FUSE & FUSEHOLDER

632.600



F **DIN 41668** **EN 60127-2-4** **ac**

As assembly with two pigtails on various form and length
Assemblato con due cappucci con terminali a lunghezza custom



10 pz. [std. packaging ~ conf. standard]
500 pz. [ind. packaging ~ conf. industriale]

Body Corpo	Glass Vetro	Extinguishing agent Polvere spegنيarco	<input checked="" type="checkbox"/>
Voltage Tensione	60 V - 150 V - 250 V	Contacts material Materiale contatti	CuZn
Soldering Saldatura	EN 60068-2-20	Contacts finishing Finitura contatti	Ni

TIME CURRENT / TEMPI DI FUSIONE

RATED CURRENT CORRENTE NOMINALE	1.15 x I _n		2.0 x I _n		2.75 x I _n		4 x I _n		10 x I _n	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
50 mA - 100 mA 125 mA - 16 A	1 h	120 s	2 ms	200 ms	1 ms	8 ms	0	0	5 ms	80 ms

CODE	I. RATING I. NOM.	BREAKING CAPACITY CAPACITÀ DI ROTTURA	V.D. C.D.T.	VOLTAGE TENSIONE	POW. DIS. POT. DIS.	MELTING RATING FUSIONE NOM.
632.602	32 mA	35 A	13 V	250 V	1,6 W	Arich./Onreq.
632.603	40 mA	35 A	12,5 V	250 V	1,6 W	Arich./Onreq.
632.604	50 mA	35 A	10 V	250 V	1,6 W	Arich./Onreq.
632.605	63 mA	35 A	8 V	250 V	1,6 W	Arich./Onreq.
632.606	80 mA	35 A	7 V	250 V	1,6 W	Arich./Onreq.
632.607	100 mA	35 A	6 V	250 V	1,6 W	Arich./Onreq.
632.608	125 mA	35 A	5,5 V	250 V	1,6 W	Arich./Onreq.
632.609	160 mA	35 A	5 V	250 V	1,6 W	Arich./Onreq.
632.610	200 mA	35 A	4 V	250 V	1,6 W	Arich./Onreq.
632.611	250 mA	35 A	3,5 V	250 V	1,6 W	Arich./Onreq.
632.612	315 mA	35 A	3 V	250 V	1,6 W	Arich./Onreq.
632.613	400 mA	35 A	2,5 V	250 V	1,6 W	Arich./Onreq.
632.614	500 mA	35 A	2 V	250 V	1,6 W	Arich./Onreq.
632.615	630 mA	35 A	1,8 V	250 V	1,6 W	Arich./Onreq.
632.616	800 mA	35 A	1,5 V	250 V	1,6 W	Arich./Onreq.
632.617	1 A	35 A	0,5 V	250 V	1,6 W	Arich./Onreq.
632.618	1,25 A	35 A	0,4 V	250 V	2,5 W	Arich./Onreq.
632.619	1,6 A	35 A	0,4 V	250 V	2,5 W	Arich./Onreq.
632.620	2 A	35 A	0,3 V	250 V	2,5 W	Arich./Onreq.
632.621	2,5 A	35 A	0,25 V	150 V	2,5 W	Arich./Onreq.
632.622	3,15 A	35 A	0,25 V	150 V	4 W	Arich./Onreq.
632.623	4 A	40 A	0,25 V	150 V	4 W	Arich./Onreq.
632.624	5 A	50 A	0,2 V	60 V	4 W	Arich./Onreq.
632.625	6,3 A	63 A	0,2 V	60 V	4 W	Arich./Onreq.
632.626	8 A	80 A	0,2 V	60 V	4 W	Arich./Onreq.
632.627	10 A	100 A	0,2 V	60 V	4 W	Arich./Onreq.
632.628	12,5 A	100 A	0,2 V	60 V	4 W	Arich./Onreq.
632.630	16 A	100 A	0,2 V	60 V	4 W	Arich./Onreq.

⓪ Not mentioned in the standards / Non menzionato negli standards

All Pictures shown are for illustration purpose only. Specifications are subject to change without notice

Le immagini sono inserite a scopo illustrativo. I prodotti possono subire modifiche.



ELECTRONIC
ELECTROMECHANICAL
COMPONENTS
PARTNER & DEALER



Via Monferrato, 43
20098 San Giuliano Milanese
I T A L Y

T. +39 02 55.60.61.01
F. +39 02 55.60.71.43

www.klemi-contact.com