


All rights are strictly reserved. Reproduction or disclosure to third parties in any form whatever is not permitted without written authorization from the proprietor. A violation is punishable.



Klemi Contact
The connectables
FUSE & FUSEHOLDER

1038.100



FF / gR **IEC 60269-4** **ac**



10 pz. [std. packaging ~ conf. standard]
100 pz. [ind. packaging ~ conf. industriale]

Body Corpo	Ceramic Ceramica	Extinguishing agent Polvere spegنيarco	<input checked="" type="checkbox"/>
Voltage Tensione	690 V	Contacts material Materiale contatti	CuZn
		Contacts finishing Finitura contatti	Ni

TIME CURRENT / TEMPI DI FUSIONE

RATED CURRENT CORRENTE NOMINALE	2.1 x I _n	4 x I _n	10 x I _n
1 A - 32 A	A rich. / On req.	A rich. / On req.	A rich. / On req.

CODE	I. RATING I. NOM	BREAKING CAPACITY CAPACITÀ ROTTURA	V.D. C.D.T.	POW. DIS. POT. DIS.	MELTING RATING FUSIONE NOM.	
					PRE-ARCING	OPERATING
1038.117	1 A	160.000 A	800 mV	0.8 W	0.17 A ² s	0.48 A ² s
1038.118	1,25 A	160.000 A	1200 mV	1.5 W	0.18 A ² s	0.55 A ² s
1038.119	1,5 A	160.000 A	800 mV	1.2 W	0.31 A ² s	0.80 A ² s
1038.120	2 A	160.000 A	350 mV	1.3 W	0.94 A ² s	2.50 A ² s
1038.121	2,5 A	160.000 A	560 mV	1.4 W	1.65 A ² s	4.50 A ² s
1038.122	3 A	160.000 A	500 mV	1.5 W	2.83 A ² s	7.80 A ² s
1038.123	4 A	160.000 A	425 mV	1.7 W	6.7 A ² s	12 A ² s
1038.124	5 A	160.000 A	180 mV	0.9 W	7.5 A ² s	30 A ² s
1038.125	6 A	160.000 A	233 mV	1.4 W	8.5 A ² s	40 A ² s
1038.126	8 A	160.000 A	237 mV	1.9 W	5.4 A ² s	35 A ² s
1038.127	10 A	160.000 A	210 mV	2.1 W	6.7 A ² s	55 A ² s
1038.128	12,5 A	160.000 A	224 mV	2.8 W	11 A ² s	90 A ² s
1038.130	16 A	160.000 A	187 mV	3.0 W	19 A ² s	140 A ² s
1038.131	20 A	160.000 A	185 mV	3.7 W	39 A ² s	245 A ² s
1038.132	25 A	160.000 A	172 mV	4.3 W	69 A ² s	425 A ² s
1038.133	30 A	160.000 A	163 mV	4.9 W	107 A ² s	675 A ² s
1038.134	32 A	160.000 A	159 mV	5.1 W	154 A ² s	945 A ² s

Klemi Contact pursues a policy of continuous development and reserves the right to make changes or updates without notice, the design, materials or technical specifications of any product, the information contained in this file/datasheet and to stop distributing any product described. Images are included for illustrative purposes. The products are subject to change.

Klemi Contact persegue una politica di continuo sviluppo e si riserva il diritto di apportare modifiche o aggiornare senza preavviso, il design, i materiali o le specifiche tecniche di qualsiasi prodotto, le informazioni contenute in questo file/scheda dati e di interrompere la distribuzione di qualsiasi prodotto descritto. Le immagini sono inserite a scopo illustrativo. I prodotti possono subire modifiche.



ELECTRONIC
ELECTROMECHANICAL
COMPONENTS
PARTNER & DEALER

FOLLOW US ON SOCIAL MEDIA!



Via Monferrato, 43
20098 San Giuliano Milanese
ITALY

T. +39 02 55.60.61.01
F. +39 02 55.60.71.43

www.klemi-contact.com