


All rights are strictly reserved. Reproduction or disclosure to third parties in any form whatever is not permitted without written authorization from the proprietor. A violation is punishable.



Klemi Contact
The connectables
FUSE & FUSEHOLDER

1038.300



T / aM

IEC 60269-1

IEC 60269-2

ac



10 pz. [std. packaging ~ conf. standard]
100 pz. [ind. packaging ~ conf. industriale]

Body Corpo	Ceramic Ceramica	Extinguishing agent Polvere spegningarco	<input checked="" type="checkbox"/>
Voltage Tensione	400 V / 500 V	Contacts material Materiale contatti	CuZn
		Contacts finishing Finitura contatti	Ni

TIME CURRENT / TEMPI DI FUSIONE

RATED CURRENT CORRENTE NOMINALE	2.1 x I _n	4 x I _n	10 x I _n
160 mA - 32 A	A rich. / On req.	A rich. / On req.	A rich. / On req.

CODE	I. RATING I. NOM.	BREAKING CAPACITY CAPACITÀ DI ROTTURA	VOLTAGE TENSIONE	POW. DIS. POT. DIS.	MELTING RATING FUSIONE NOM.
1038.309	160 mA	120 kA	500V	0.24 W	3.0 A ² s
1038.311	250 mA	120 kA	500V	0.36 W	4.0 A ² s
1038.314	500 mA	120 kA	500V	0.49 W	6.5 A ² s
1038.317	1 A	120 kA	500V	0.10 W	9.5 A ² s
1038.320	2 A	120 kA	500V	0.18 W	40 A ² s
1038.323	4 A	120 kA	500V	0.31 W	90 A ² s
1038.325	6 A	120 kA	500V	0.32 W	120 A ² s
1038.326	8 A	120 kA	500V	0.52 W	220 A ² s
1038.327	10 A	120 kA	500V	0.55 W	300 A ² s
1038.328	12 A	120 kA	500V	0.63 W	380 A ² s
1038.330	16 A	120 kA	500V	0.92 W	550 A ² s
1038.331	20 A	120 kA	400V	0.96 W	950 A ² s
1038.332	25 A	120 kA	400V	1.40 W	1300 A ² s
1038.334	32 A	120 kA	400V	1.80 W	3000 A ² s

Klemi Contact pursues a policy of continuous development and reserves the right to make changes or updates without notice, the design, materials or technical specifications of any product, the information contained in this file/datasheet and to stop distributing any product described. Images are included for illustrative purposes. The products are subject to change.

Klemi Contact persegue una politica di continuo sviluppo e si riserva il diritto di apportare modifiche o aggiornare senza preavviso, il design, i materiali o le specifiche tecniche di qualsiasi prodotto, le informazioni contenute in questo file/scheda dati e di interrompere la distribuzione di qualsiasi prodotto descritto. Le immagini sono inserite a scopo illustrativo. I prodotti possono subire modifiche.



ELECTRONIC
ELECTROMECHANICAL
COMPONENTS
PARTNER & DEALER

FOLLOW US ON SOCIAL MEDIA!



Via Monferrato, 43
20098 San Giuliano Milanese
ITALY

T. +39 02 55.60.61.01
F. +39 02 55.60.71.43

www.klemi-contact.com