



CUT & STRIP
TAGLIA & SPELA



70 mm²



AM 3850

CUT & STRIP with Rotary Cutting Module

Metzner

Max. cable outer diameter Diametro massimo del cavo	20 mm
Cable length Lunghezza del cavo	75 mm - 999m
Cable size range stranded / solid Sezione cavo multi-trefolo / unipolare	0.5 - 70 mm ² / 0.5 - 10 mm ²
Feeding speed Velocità trascinalimento cavo	180 m/min
Pull-off length max. 1st / 2nd side Spell. Max. 1/2	210mm / 110mm
Power supply Alimentazione elettrica	230 V, 50/60 Hz, 2 A
Pneumatic supply Alimentazione pneumatica	6 bar
Weight Peso	130 Kg
Dimensions (LxWxH) Dimensioni (LxPxH)	885 x 849 x 485 mm
Various Varie	PC/SPS - interface for printers, peripherals and network PC/SPS – interfaccia per stampanti, per periferiche e di rete

CABLE PROCESSING

CUT-TO-LENGTH	
STRIPPING WITH PARTIAL AND FULL PULL-OFF	
WINDOW STRIPPING	
EXTREMELY LONG PULL-OFF IN MULTIPLE STAGES	
JACKET STRIPPING OF MULTI CONDUCTOR CABLES	
FLAT RIBBON STRIPPING AND INNER STRANDS	
INCISE CUTTING AND LENGTH SLITTING	
STRIPPING OF VERY THIN INSULATIONS	
METAL BRAID STRIPPING WITH PROTECTION CAP	
MULTI-STEP STRIPPING	
MULTI-STEP PROCESSING OF COAXIAL CABLES	

FEATURES

Double-blade system® and rotary cut for processing cables up to 185mm²
Sistema a doppia lama e taglio rotativo per cavi fino a 185 mm²

Outstanding cutting force
Forza di taglio eccezionale

High productivity & High-precision rotary cut
Alta produttività e taglio rotativo ad alta precisione

Belt feeds
Trascinamento a nastro

One operation – two processes
Un'operazione – due processi

All Pictures shown are for illustration purpose only. Specifications are subject to change without notice

Le immagini sono inserite a scopo illustrativo. I prodotti possono subire modifiche.



ELECTRONIC
ELECTROMECHANICAL
COMPONENTS
PARTNER & DEALER



Via Monferrato, 43
20098 San Giuliano Milanese
I T A L Y

T. +39 02 55.60.61.01
F. +39 02 55.60.71.43

www.klemi-contact.com